

CL-P60250-D 250W

60 (6×10) 156×156mm

Polycrystalline PV modules



4BB (4 bus bar)
technology

5

YEAR

Manufacturing Warranty

12


YEAR WARRANTY

90% Power Output

25

YEAR WARRANTY

80% Power Output



Power tolerance (0~+3%) to ensure the high reliability of power output



Modules certified by TÜV to with stand high level of wind loads (2400 Pa) and snow loads (5400 Pa)



Special PV Module Insurances by world leading insurance company guarantees the benefit of PV investors and PV module users




Junction box and bypass diods guarantee the modules free of overheating and "hot spot effect"

WHY ABI-SOLAR?

- PV modules are designed for maximum efficiency when used in insolation conditions of the Central European region.
- Each PV module by Abi-Solar is tested to verify its characteristics and specifications.
- Modules certified by global testing facilities: IEC61215, IEC61730, CE, ROHS.
- Manufacturing with international quality standarts and environment management system: ISO9001 and ISO14001.
- Maximum power and performance at minimal price ensure fast return of investments.
- Compatability with both on-grid and off-grid PV systems ga-
rateed.

MECHANICAL DRAWINGS



MECHANICAL SPECIFICATIONS

Cell type	Poly Crystalline 156x156 mm
Number of cells	60 (6x10)
Dimensions (AxBxC)	1640x991x35 mm
Weight	19 kg
Front Glass	3.2 mm tempered low iron glass
Frame	Anodized aluminum
Junction Box	IP67 with bypass diodes
Connector	MC4 compatible
Output cables	TUV, length ± 900mm, 4.0mm ²

ELECTRICAL CHARACTERISTICS

	STC	NOCT
Maximum Power (Pmax)	250W	181,5W
Short Circuit Current (Isc)	8.81A	7.01A
Open Circuit Voltage (Voc)	37.6V	34.57V
Maximum Power Current (Impp)	8.2A	6.49A
Maximum Power Voltage (Vmpp)	30.5V	28.0V
Module Efficiency	15.29%	
Power Tolerance	0~+3%	

STC irradiance: 1000 W/m² module temperature: +25 °C AM=1,5

NOCT irradiance: 800 W/m² module temperature: +20 °C AM=1,5


TEMPERATURE CHARACTERISTICS

Nominal Operating Cell Temperature (NOCT)	45 °C ±2 °C
Temperature Coefficient of Pmax	-0.44% °C
Temperature Coefficient of Voc	-0.34% °C
Temperature Coefficient of Isc	0.06% °C


PACKING CONFIGURATION

Container	20'GP	40'GP
Pieces per pallet	30	30
Pallets per container	12	28
Pieces per container	360	840

V-I Curves at different irradiances



Power/Voltage/Current curves at different temperatures



SYSTEM INTEGRATION PARAMETERS


Maximum System Voltage	VDC 1000V
Maximum Series Fuse	15A
Operating Temperature	-40 °C ... +85 °C
Maximum snow load (IEC 61215)	5400Pa
Number of bypass diodes	2 or 4

QUALIFICATIONS AND CERTIFICATES



IEC 61215
IEC 61730

INDUSTRY-LEADING WARRANTY BASED ON NOMINAL POWER



United Kingdom

44 Main Street, Douglas,
South Lanarkshire,
ML11 0QW, UK
+441315659030

Poland

ul. Józefa Ignacego
Kraszewskiego 36/128,
30-110 Kraków
+48 12 307-25-43

Ukraine

13-B, Revuts'kogo street,
Kyiv, Ukraine,
02091
+380 44 545-71-04

Russia

47, Nizhniaya
Pervomaiskaya street,
Moscow, 105203
+7 495 975-98-73